MATERIAL SAFETY DATA SHEET

Manufacturer's Name	Americover	Emergency Telephone Numbers	800-747-6095
Address	2060 Wineridge Pl., Ste.B Escondido, CA 92029	Other Information	760-747-6095
Signature of Person Responsible for Preparation	*[signature]*	Date Prepared	August 10, 2001

Section 1 - IDENTITY

Common Name: (Used on Label) (Trade Name Synonyms)	VaporBlock 10 & 15	CAS Number(s)	26221-73-8 25213-02-9
Chemical Name	Copolymer of Ethylene and Hexene	Family	Polyolefin
Formula	(CH2 - CH2) n		

Section 2 - HAZARDOUS INGREDIENTS

Principal Hazardous Component(s) - Chemical and Common Na	%	Threshold Limit Value (units)
None Known		

Section 3 - PHYSICAL & CHEMICAL CHARACTERISTICS (Fire & Explosion Data)

Boiling Point	Not Applicable (N/A)	Specific Gravity	0.93	Vapor Pressure, mmHg	N/A
Percent Volatile by Volume (%)	0.01%	Vapor Density	N/A	Evaporation Rate	N/A
Solubility in Water	Insoluble in Water	Reactivity in Water	Not Reactive in Water		
Appearance and Odor	Blue, Odorless Plastic sheet.				

Flash Point	N/A	Flammability Limits in Air, by Volume (%)	Lower N/A	Upper N/A	Auto Ignition Temperature	> 650 F (estimated)

Extinguisher Media Use water spray, dry chemical, foam or carbon dioxide

Special Fire Fighting Proced. Fire fighters should wear self-contained breathing apparatus when there is a possibility of exposure to smoke, fumes or hazardous decomposition products. If possible, water should be applied as a spray from a fogging nozzle since this material is a surface burning material.

Unusual Fire and Explosion Hazards None

Section 4 - PHYSICAL HAZARDS

Stability			Conditions to Avoid	Temperatures over 570 F will release combustible gases.
Unstable				
Stable	X			
Incompatibility (Materials to Avoid)			Strong oxidizers. May react with free halogens.	
Hazardous Decomposition Products			The following combustion products may be generated: Carbon dioxide, carbon monoxide, water vapor, and trace volatile organic compounds.	

Hazardous Polymerization	May Occur			Conditions to Avoid	N/A
	Will not Occur	X			